

PNEUMATIC STRAPPING TOOL FOR PP/PET STRAP

ST-POLI 10-19 LT FLAT AND ROUND SURFACES PNEUMATIC STRAPPING TOOL FRICTION WELD SEAL



Chart of types		
MODEL	ITEM.NO.	STRAP WIDTH
ST-POLI10LT	109.100.310	10-11 mm. 3/8"
ST-POLI13LT	109.130.310	12-13 mm. 1/2"
ST-POLI16LT	109.160.310	16 mm. 5/8"
ST-POLI19LT	109.190.310	19 mm. 3/4"

Technical data	
Strap quality	PP/PET
Joint type	friction weld seal
Package type	flat / round (min. 50 cm ø)
Strap width	10-13-16-19 mm / 3/8"- 1/2"- 5/8"- 3/4"
Strap thickness	0,4-1,0 mm. / .015" - .040"
Max tension	1.500 N / 153 Kg
Max tension speed	11 m/min
Air pressure	6/7 bar / 85 -100 PSI
Air consumption for tensioning	9 lt/sec
Air consumption for welding	12 lt/sec
Weight	4,50 kg / 9.9 lbs

ST-POLI 16-19 MT FLAT AND ROUND SURFACES PNEUMATIC STRAPPING TOOL FRICTION WELD SEAL



Chart of types		
MODEL	ITEM.NO.	STRAP WIDTH
ST-POLI16MT	115.160.710	16 mm. 5/8"
ST-POLI19MT	115.190.710	19 mm. 3/4"

Technical data	
Strap quality	PP/PET
Joint type	friction weld seal
Package type	flat / round (min. 50 cm ø)
Strap width	16-19 mm / 5/8" - 3/4"
Strap Thickness	0,7-1,27 mm. / .027" - .050"
Max tension	2.600 N / 265 Kg
Max tension speed	9 m/min
Air pressure	6/7 bar / 85 -100 PSI
Air consumption for tensioning	9 lt/sec
Air consumption for welding	12 lt/sec
Weight	4,60 kg / 10,14 lbs

ST-POLI 16-19 HT FLAT SURFACES PNEUMATIC STRAPPING TOOL FRICTION WELD SEAL



Chart of types		
MODEL	ITEM.NO.	STRAP WIDTH
ST-POLI16HT	110.160.630	16 mm. 5/8"
ST-POLI19HT	110.190.630	19 mm. 3/4"

Technical data	
Strap quality	PP/PET
Joint type	friction weld seal
Package type	flat
Strap width	16-19 mm / 5/8" - 3/4"
Strap Thickness	0,9 - 1,27 mm. / .035" - .050"
Max tension	4.000 N / 408 Kg
Max tension speed	7 m/min
Air pressure	6/7 bar / 85 -100 PSI
Air consumption for tensioning	9 lt/sec
Air consumption for welding	12 lt/sec
Weight	4,65 kg / 10,25 lbs